

# REFRIGERATION PRODUCTS

## SK LIQUID LINE FILTER DRIERS

### FEATURES:

- Solid Core
- Prevents refrigeration system from being polluted
- Epoxy paint
- Silica XH-09
- High moisture and acid removal capability
- Copper ends
- Helps protect the system from damaging contaminants



### SK LIQUID LINE FILTER DRIER

PART NO.	MAXIMUM WORKING PRESSURE	LIQUID FLOW CAPACITY (TONS)							CONNECTIONS					
		R134A	R12	R22	R410	R407C	R404A R507	R502	ODF (IN.)	SAE (IN.)	A (IN.)	B (IN.)	C (IN.)	D (IN.)
SK-052	600	2.1	1.7	2.2	2.2	2.2	1.5	1.5		1/4	4.81		3.00	2.64
SK-052S	600	3.6	3.0	4.0	4.0	4.0	2.6	2.6	1/4		4.44	3.69	3.00	2.64
SK-053	600	4.6	3.8	5.0	5.0	5.0	3.3	3.3		3/8	5.13		3.00	2.64
SK-053S	600	6.7	5.5	7.3	7.3	7.3	4.8	4.7	3/8		4.50	3.63	3.00	2.64
SK-082	600	2.1	1.7	2.2	2.2	2.2	1.5	1.5		1/4	5.63		3.80	2.64
SK-082S	600	3.6	3.0	4.0	4.0	4.0	2.6	2.6	1/4		5.25	4.50	3.80	2.64
SK-083	600	5.5	4.5	5.9	5.9	5.9	4.0	3.9		3/8	5.94		3.80	2.64
SK-083S	600	7.4	6.1	8.1	8.1	8.1	5.4	5.3	3/8		5.31	4.44	3.80	2.64
SK-084	600	9.2	7.6	10.0	10.0	10.0	6.7	6.5		1/2	6.19		3.80	2.64
SK-084S	600	10.4	8.5	11.2	11.2	11.2	7.5	7.3	1/2		5.38	4.38	3.80	2.64
SK-163	600	6.1	5.0	6.6	6.6	6.6	4.4	4.3		3/8	6.88		4.75	2.64
SK-163S	600	8.2	6.8	9.0	9.0	9.0	6.0	5.8	3/8		6.25	5.25	4.75	2.64
SK-164	600	12.2	10.0	13.2	13.2	13.2	8.8	8.6		1/2	7.06		4.75	2.64
SK-164S	600	14.6	12.0	15.9	15.9	15.9	10.5	10.3	1/2		6.31	5.19	4.75	2.64
SK-165	600	18.3	15.0	19.9	19.9	19.9	13.2	12.9		5/8	7.50		4.75	2.64
SK-165S	600	18.3	15.0	19.9	19.9	19.9	13.2	12.9	5/8		6.56	5.19	4.75	2.64
SK-167S	500	20.1	16.5	21.8	21.8	21.8	14.5	14.2	7/8		7.13	5.50	4.75	2.64
SK-304	500	14.1	11.6	15.4	-	15.4	10.2	10.0		1/2	9.88		7.50	3.15
SK-304S	500	15.4	12.7	16.8	-	16.8	11.1	10.9	1/2		9.06	8.06	7.50	3.15
SK-305	500	19.2	15.8	20.9	-	20.9	13.9	13.6		5/8	10.31		7.50	3.15
SK-305S	500	20.7	17.0	22.5	-	22.5	14.9	14.6	5/8		9.31	8.06	7.50	3.15
SK-307S	500	28.0	23.0	30.4	-	30.4	20.2	19.8	7/8		9.88	8.38	7.50	3.15
SK-415	500	23.1	19.0	25.2	-	25.2	16.7	16.4		5/8	10.44		7.25	3.66
SK-415S	500	23.1	19.0	25.2	-	25.2	16.7	16.4	5/8		9.44	8.19	7.25	3.66
SK-417S	500	28.6	23.5	31.1	-	31.1	20.6	20.2	7/8		9.88	8.19	7.25	3.66
SK-419S	500	31.7	26.1	34.5	-	34.4	22.9	22.4	1 1/8		10.38	8.56	7.25	3.66