

empackEmpack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571**PRODUCT: Emzone Ultimate Shine Spray - 400g****CODE: 044019****Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Identity..... Emzone Ultimate Shine Spray - 400g
 Product Item Numbers..... 044019
 Manufactured by..... Empack Spraytech Inc.
 98 Walker Drive
 Brampton
 Ontario
 Canada
 L6T 4H6
 905-792-6571
 24 hour emergency telephone number..... CANUTEC: (613)-996-6666 collect.
 Recommended Use..... Provides uniform shine on vinyl, leather, rubber and plastic surface.
 Consumer Commodity..... Yes.
 Hazard Ratings:
 HMIS..... Health: 2 Fire: 4 Reactivity: 0.
 NFPA Rating..... Health: 2 Fire: 4 Reactivity: 0.

Section 02: HAZARDS IDENTIFICATION

Emergency Overview..... Flammable. Danger. Poison. Contents under pressure. May catch fire. Contents may be harmful. Do not swallow . Do not puncture. Do not burn. Do not get in eyes or clothing. KEEP OUT OF REACH OF CHILDREN .
 Potential Health Effects:
 Eye Contact..... May cause irritation, redness and pain.
 Skin Contact..... Can cause skin irritation. Prolonged or repeated contact may dry the skin.
 Ingestion..... Harmful if swallowed.
 Inhalation..... Prolong Inhalation of content may cause irritation.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
Heptane	142-82-5	60-100
Propane	74-98-6	10-30
Isobutane	75-28-5	10-30
Silicone	63148-62-9	5-10

Section 04: FIRST AID MEASURES

Eye Contact..... Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.
 Skin Contact..... Wash thoroughly with soap and lukewarm water.
 Ingestion..... If swallowed, get medical attention immediately. Do not induce vomiting .
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
 Additional Information..... Note to the doctor; treat symptomatically.

Section 05: FIRE FIGHTING MEASURES

Flammability Class..... Flammable.
 Extinguishing Media..... Carbon dioxide, dry chemicals, foam or water fog.
 Sensitivity to Mechanical Impact..... Not expected to be sensitive.
 Sensitivity to Static Discharge..... Not expected to be sensitive.

Section 06: ACCIDENTAL RELEASE MEASURES

Spills and Leaks..... Large spill or leak is unlikely in aerosol containers. If spill or leak occurs, ventilate enclosed spaces and disperse gas with floor-level forced-air ventilation. Exhaust vapours outdoors. Do not smoke or operate internal combustion engines. Remove flames and heating elements.

Section 07: HANDLING AND STORAGE

Handling..... Avoid contact with heat, sparks and flame. Avoid contact with eyes, skin, and clothing. Keep container tightly closed. Use with adequate ventilation.

PRODUCT: Emzone Ultimate Shine Spray - 400g

CODE: 044019

Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye/Type..... Safety glasses with side-shields.
 Skin/Type..... Use gloves and protective clothing against cold temperature made from viton, butyl rubber, PVC, neoprene or nitrile.
 Respiratory/Type..... Not required on a short-term basis or if exhaust ventilation is provided. Use approved NIOSH respirators for emergencies.
 Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.

Exposure Limits

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Heptane	400 ppm	500 ppm	500 ppm	Not available	85 ppm for n-Heptane, 440 ppm for a ceiling conc.
Propane	2,500 ppm	Not available	1,000 ppm	Not available	1,000 ppm
Isobutane	800 ppm	1000 ppm	800ppm	Not available	800 ppm (TWA)
Silicone	Not available	Not available	Not available	Not available	No data available

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State..... Aerosol.
 Physical Appearance..... Clear mist.
 Odour..... Hydrocarbons.
 Odour Threshold (ppm)..... Not available.
 pH..... Not applicable.
 Vapour Pressure (psig)..... 60- 80.
 Vapour Density (Air=1)..... Not available.
 Evaporation Rate (n-Butyl Acetate = 1)..... > 1 .
 Initial Boiling Point/Boiling Range (° C)..... 140-150.
 VOC Content..... Not available.
 Specific Gravity (liquid)..... 0.710-0.770 .
 Specific Gravity (Aerosol)..... 0.620- 0.660.
 Solubility in water..... Nil.
 Aerosol Flame Projection..... Not available .
 Auto Ignition Temperature (Propellant), ° C.. 470.85 °C (888.5 °F) .
 Flashback..... Yes.
 Flash Point (° C), Method..... -104 °C (-156°F).
 Lower Flammable Limit (% Vol)..... 2.1.
 Upper Flammable Limit (% Vol)..... 9.5.

Section 10: STABILITY AND REACTIVITY

Stability..... Stable at normal temperatures and pressures.
 Incompatibility..... Strong oxidizing agents.
 Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.
 Hazardous Products of Decomposition..... May form carbon dioxide and carbon monoxide, various hydrocarbons.
 Hazardous Polymerization..... Will not occur.

Section 11: TOXICOLOGICAL INFORMATION

Route of Exposure..... Skin contact, Eye contact, Inhalation and Ingestion.
 Effects of Acute Exposure..... High vapor/aerosol concentrations may be irritating to eyes. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. In high concentrations, vapors and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Ingestion may result in vomiting.
 Effects of Chronic Exposure..... Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Prolong contact may defat and dry the skin, leading to discomfort and dermatitis .
 Carcinogenicity of Material..... Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP.
 Reproductive Effects..... No information is available, and no adverse effects are expected.
 Teratogenicity..... No information is available, and no adverse effects are expected.
 Mutagenicity..... No information is available, and no adverse effects are expected.

Toxicological Data

Ingredients	LC50	LD50
Heptane	103,000 mg/L (4hrs - rat)	>15,000 mg/kg (rat - oral); >2,000 mg/kg (rabbit - dermal)
Propane	>800,000 ppm (15 min,Inh.rat)	Not available
Isobutane	658 mg/L (4hrs,rat)	Not available

PRODUCT: Emzone Ultimate Shine Spray - 400g

CODE: 044019

Section 11: TOXICOLOGICAL INFORMATION

Ingredients	LC50	LD50
Silicone	>2,000 mg/kg (rabbit - oral)	>15,400 mg/kg (rat - oral)

Section 12: ECOLOGICAL INFORMATION

Environmental..... Very toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Heptane: Toxicity to fish: LC50 1.284 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 0.1 mg/L, 96 hrs; Toxicity to algae: EL50 4.338 mg/L, 72 hrs.

Section 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

Section 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... AEROSOLS, Class 2.1, UN1950.
 DOT (US-Road)..... AEROSOLS, Class 2.1, UN1950, LTD. QTY. OR ORM-D.
 IMDG (International- Marine)..... AEROSOLS, Class 2.1, UN1950.
 IATA (International- Air)..... AEROSOLS, Class 2.1, UN1950, LTD QTY.

Section 15: REGULATORY INFORMATION

Canada..... WHMIS Classification. A: Compressed gas. B5: Flammable Aerosol. D2B: Material causing other toxic Materials.
 USA..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. OSHA (29CFR 1910.1200) Classification: Compressed Gas. HIMS Classifications: see section 01.

Section 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System.

Prepared by Regulatory Affairs
 Preparation Date..... Sep30/13
 Last Revision Date Sep19/14