

## SPECIFICATIONS FOR NATURAL FIBER

**Product Type:** Air Filter

### Standard Filter – Par 5, Par 75, Par 10 and Par 20 Pad Specifications

**Color:** Blue or Green for ANSI/ UL STD 900  
Red for FMVSS302

**Contents:** Hog Hair  
Coconut Fiber Twisted Rope  
Coconut Fiber Bristle Cut Ends  
Latex Based Binder  
Scrim Backing

**Binder Content:** Latex polymer and clay filler, 60% of pad weight is Fiber, 40% of pad weight is Binder.

**Scrim:** Polyester scrim with a Machine Direction = (12) double stacked threads @ 70 denier and a Cross Direction = 4 threads @ 150 denier.

**Certification:** Meets or exceeds the standard per customer order:  
ANSI/ UL STD 900 (for air filter applications)  
FMVSS302 (for motor vehicle interior materials applications)

**Thickness:** PAR 5 = ½": 5/8" +/- 1/8" actual  
PAR 75 = ¾": 3/4" +/- 1/8" actual  
PAR 10 = 1" : 1" +/- 1/8" actual  
PAR 20 = 2" : 2" +/- 1/8" actual

**Width / Length:** Cut to size, +0.250 inches, -0.250 inches  
Minimum Width 8"  
Maximum Width 72"

**Weight:** PAR 5 = ½": 2.25 +/- .25 oz./sq. ft.  
PAR 75 = ¾": 2.65 +/- .25 oz./sq. ft.  
PAR 10 = 1" : 2.85 +/- .25 oz./sq. ft.  
PAR 20 = 2" : 4.00 +/- .25 oz./sq. ft.

Filter media is bacteriostatic, will not support growth of mold, mildew or bacteria.