



Connected Thermostats

		Description	Model	Schedule Options				User Interface	Application										Power Method	Features and Functions																		
Network Connection				Program Options	Temporary Override	Permanent Hold	Vacation Hold		Stages	Gas, Oil or Electric	Heat Pump	Millivolt	Linevolt	Selectable Residential and Light Commercial	Dual fuel	Balance Point Lockout	Upstage Timer & Drip Settings	Humidification Control	Dehumidification Control	Ventilation Control	Demand Response	Permanent Memory Retention	Selectable Auto or Manual Changeover	Auxiliary Heat Lockout	Adaptive Intelligent Recovery	Temperature Setpoint Limits	Keypad Lockout	Programmable & Circulation Fan	Tri-Lingual Language Options	Wireless Outdoor Sensor	Wired Outdoor Sensor	Dealer Info On Screen	Display Size (Viewable)	Continuous Backlighting	Service Reminders	Limited Warranty	Wiring Terminals	Accessories Included
WIFI		T10 Pro Smart with RedLINK® Sensor	THX321WFS2001W	Geofence, 7-day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•				•	•	•	•	•	C-Wire	•	•	•	•	•	•	Via internet	•	•	•	•	5 Year	R, RC, C, W, W2-AUX, E, 0/B, Y, Y2, G, L, K, U, S and S	C7189R2002 wireless temp/humidity/motion sensor, UWP mounting system, decorative cover plate, & mounting hardware				
		T10 Pro Smart without Sensor	THX321WF2003W	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•				•	•	•	•	•	C-Wire	•	•	•	•	•	•	Via internet	Lockouts only, no display	•	•	•	•	5 Year	R, RC, C, W, W2-AUX, E, 0/B, Y, Y2, G, L, K, U, S and S	UWP mounting system, decorative cover plate, & mounting hardware			
WIFI		T6 Pro Smart	TH6320WF2003	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•				•	•	•	•	•	C-Wire	•	•	•	•	•	•	Via internet	Lockouts only, no display	•	•	•	•	5 Year	R, RC, C, W, W2-AUX, E, 0/B, Y, Y2, G, L, K, S and S	UWP mounting system, decorative cover plate, & mounting hardware			
		T6 Pro Smart	TH6220WF2006	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•				•	•	•	•	•	C-Wire	•	•	•	•	•	•	Via internet	Lockouts only, no display	•	•	•	•	5 Year	R, RC, C, W, W2-AUX, E, 0/B, Y, Y2, G, L, K, S and S	UWP mounting system, decorative cover plate, & mounting hardware			
WIFI		9000 Smart	TH9320WF5003	7-Day or NP	•	•	•	Touchscreen	Up to 2 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•				•					C-Wire	•	•	•	•	•	•	Via internet			8 sq. in.	•	Filter, humidifier pad only	5 Year	R, RC, C, W-0/B, Y, G, W2-AUX/E, Y2, L, K	Mounting hardware			
		Vision PRO® 8000 Smart	TH8321WF1001	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•				•	•	•	•	•	C-Wire	•	•	•	•	•	•	Via internet	•	•	•	•	5 Year	R, RC, W2-AUX/E, Y, Y2, G, C, K, S1, S1, W-0/B, U1, U1, A-L/A	Mounting hardware				
Via RedLINK Internet Gateway		YTHX9421R5085WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•			•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IAQ - R, C, Equipment Interface Module - R, C, RH, RC, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, S1, S1, S2, S2, S3, S3, S4, A, B, C, D	THM5421R1021 Equipment Interface Module and 2 duct sensors			
			YTHX9421R5101WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•			•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IAQ - R, C, Equipment Interface Module - R, C, RH, RC, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, S1, S1, S2, S2, S3, S3, S4, A, B, C, D	THM5421R1021 Equipment Interface Module, C7089R1013 wireless outdoor sensor, and 2 duct sensor		
		YTHX9421R5127WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•			•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IAQ - R, C, Equipment Interface Module - R, C, RH, RC, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, S1, S1, S2, S2, S3, S3, S4, A, B, C, D	THM5421R1021 Equipment Interface Module, THM6000R7001 RedLINK Internet Gateway and 2 duct sensors			
			YTHX9421R7001WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•			•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IAQ - R, C, Equipment Interface Module - R, C, RH, RC, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, S1, S1, S2, S2, S3, S3, S4, A, B, C, D	THM5421R1021 Equipment Interface Module, THM6000R7001 RedLINK Internet Gateway, C7089R1004 wireless indoor sensor and 2 duct sensors		
	Prestige® IAQ	THX9421R5021WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•			•	•	•	•	•	24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	5 Year	Prestige IAQ - R & C (EIM ordered separately).	Mounting hardware			
Via RedLINK Internet Gateway	EConnect™ Wireless Comfort System	YTL9160AR1000	7-Day or NP	•	•		Soft Keys	1 Heat											Battery powered thermostat, 120/240V at EIM		•		•	•					4.53 sq. in.			3 Year	L1/L, L2/N & Load, Load	Antenna (with 2 covers white and beige) and EIM				
		TH8110R1008	7-Day or NP	•	•	•	Touchscreen	1 Heat/1 Cool**	•	•	•			•					Dual powered (battery and hardwire)	w/ Gateway	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-0/B, Y, G, S1, S1	Batteries & mounting hardware			
			TH8320R1003	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•			•	•	•	•		Dual powered (battery and hardwire)	w/ Gateway	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-0/B, W2-AUX/E, Y, Y2, G, A-L/A, K, S1, S1	Batteries & mounting hardware		
		TH8321R1001	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•			•	•	•	•	•	Dual powered (battery and hardwire)	w/ Gateway	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-0/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1, S1, S1	Batteries & mounting hardware			
		YTH8321R1002	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•			•	•	•	•	•	Dual powered (battery and hardwire)		•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	5 Year	R, RC, C, W-0/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1, U1, S1, S1	RedLINK Internet Gateway, Batteries & mounting hardware			
Z-Wave	FocusPRO® 6000 RedLINK® Programmable Kit	YTH6320R1001	5-1/5-2	•	•		Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•				•	•	•	•		Batteries at thermostat, R and C at EIM		•	•	•	•	•	•			5.09 sq. in.			5 Year	Equipment Interface Module – C, R, RC, RH, W-0/B, W2-AUX-/E, Y, Y2, G, L, RAS, RAS	EIM, Return Air Sensor, Batteries & mounting hardware				
	FocusPRO® 5000 RedLINK® Non-Programmable	YTH5320R1000	Non programmable				Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•			•	•	•	•		Batteries at thermostat, R and C at EIM		•	•	•	•	•	•			5.09 sq. in.			5 Year	Equipment Interface Module – C, R, RC, RH, W-0/B, W2-AUX-/E, Y, Y2, G, L, RAS, RAS	EIM, Return Air Sensor, Batteries & mounting hardware				
	T6 Pro Z-Wave	TH6320ZW2003	7-Day, 5-1-1, 5-2, 1 week no schedule, Z-Wave occupancy	•	•	Through Z-Wave app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•				•	•	•	•		Dual powered (battery and hardwire)		•	•	•	•	•	•			6.89 sq. in.	•	•	5 Year	C, R, RC, Y, Y2, G, D/B, W, W2, AUX, E, L, K, S and S	UWP mounting system, decorative cover plate, & mounting hardware				

Non-Connected Thermostats

	Description	Model	Scheduling	User Interface	Application				Power Method				Sensors		Display Information		Limited Warranty	Wiring Terminals		Accessories Included		
					Stages	Gas, Oil or Electric	Heat Pump	Millivolt	Linevolt		Permanent Memory Retention	Selectable Auto or Manual Changeover	Duel Fuel	Wired Outdoor Sensor	Wired Indoor Sensor	Floor/Slab Sensor	Temperature Setpoint Limits	Display Size (Viewable)	On Demand Backlighting			
	T6 Pro	TH6320U2008	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH6220U2000	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH6210U2001	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•					•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E and K	UWP mounting system, decorative cover plate, mounting hardware & batteries
	T6 Pro Hydronic	TH6100AF2004	7-day, 5-1-1, 5-2, or NP	Soft keys	1 Stage Hot Water Heat Only - No Fan					Dual powered (battery and hardwire)	•					•	•	5.44 sq. in.	•	5 Year	R, RC, C, W, S, and S	Floor sensor, UWP mounting system, decorative cover plate, mounting hardware & batteries
	T4 Pro	TH4210U2002	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•				•	3.93 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E & K	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH4110U2005	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 1 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•				•	3.93 sq. in.	•	5 Year	R, RC, W, O/B, Y, G, C, L, and K	UWP mounting system, decorative cover plate, mounting hardware & batteries	
	TL8100 Hydronic	TL8100A1008	7-Day	Soft keys	Control a line Voltage (120/240VAC) valve or pump or a 24 volt valve.	Gas or oil		•		Battery powered	•						2.67 sq. in.	•	5 Year	1, 2, 3	Mounting hardware & Batteries	
	T3 Pro Non-Programmable	TH3210U2004	NP	Soft keys	2 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•				•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, G, AUX, and E	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH3110U2008	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•				•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, and G	UWP mounting system, decorative cover plate, mounting hardware & batteries	
	Pro 3000 Non-Programmable	TH3210D1004	NP	Soft Keys	2 Heat/1 Cool – Heat Pump only		•			Dual powered (battery and hardwire)	•	Manual					1.32 sq in.	•	5 Year	R, C, O, B, Y, G, L, AUX, and E	Mounting hardware & Batteries	
		TH3110D1008	NP	Soft Keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual					1.32 sq in.	•	5 Year	R, RC, C, O, B, Y, W, and G	Mounting hardware & Batteries	
	T1 Pro Non-Programmable	TH1110D2009	NP	Soft Keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual				•	2.37 sq. in.	•	5 Year	C, R, RC, W, O/B, Y, G	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH1010D2000	NP	Soft Keys	1 Heat or 1 Cool	•		•		Dual powered (battery and hardwire)	•	Manual				•	2.37 sq. in.	•	5 Year	C, R, RC, W, Y, G	UWP mounting system, decorative cover plate, mounting hardware & batteries	
	E1 PRO Non-Programmable	TH1110E1000	NP	Softkeys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual					3.32 sq. in.	•	2 Year	R, RC, C, W, Y, G, O, and B	Wall-plate, mounting hardware, & batteries	
	The Digital Round™	T8775A1009	NP	Dial	1 Heat	•				Power stealing	•						.75 sq. in.	•	5 Year	R, W	Mounting hardware	
		T8775C1005	NP	Dial	1 Heat/1 Cool	•				Power stealing	•	Manual					.75 sq. in.	•	5 Year	R, RC, W, O/B, Y, G	Mounting hardware	
	The Round™	T87K1007	NP	Dial	1 Heat or 1 Cool	•				Power stealing						50010944-001	N/A		5 Year	R, W, Y	Mounting hardware	
		T87N1000	NP	Dial	1 Heat/1 Cool	•				Power stealing		Manual				50010944-001	N/A		5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
		T87N1026	NP	Easy-To-See™	1 Heat/1 Cool	•				Power stealing		Manual				50010944-001	N/A		5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
		T834N1002 Vertical	NP	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual				50019661-001	N/A		5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
		T8034N1007 Horizontal	NP	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual				50019661-001	N/A		5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
		T822K1000	NP	Slide switches and lever	1 Heat	•				Mechanical		Positive off				50019661-001	N/A		5 Year	R, W	Mounting hardware	
		T822K1018	NP	Slide switches and lever	1 Heat	•				Mechanical		Positive off				50019661-001	N/A		5 Year	R, W	Mounting hardware	
		T827K1009	NP	Slide switches and lever	1 Heat	•	•			Mechanical		Positive off				50019661-001	N/A		5 Year	R, W	Mounting hardware	
	TL8230	TL8230A1003	7-Day	Soft keys	1 Heat			•		3328 watts @ 208 VAC Max 3840 watts @ 240 VAC Max	•	Positive off				2.67 sq. in.	•	5 Year	4-wire DPST	Mounting hardware		
		TL7235A1003	NP	Horizontal llays	1 Heat			•		3600 watts @ 240 VAC Max 3120 watts @ 208 VAC Max	•	Positive off				2.67 sq. in.	•	3 Year	4-wire DPST	Mounting hardware		
		T410A1013 T410A1021 T410B1004	NP	Dial	1 Heat			•		22A at 120/208/240 VAC Max, 19A at 277 VAC Max		T410B has positive off			272804A Range Stop and Loading Cover	N/A		3 Year	T410A - 2-wire SPST T410B - 4-wire DPST	Mounting hardware		
		TH105PLUS	5-2	Buttons	1 Heat			•		3500 watts @ 240 VAC Max 1700 watts @ 120 VAC Max	•				•	•	3 Year	2-wire SPST	Mounting hardware			